

राष्ट्रीय उद्योग रत्न अेवोर्ड विजेता



AN ISO 9001 : 2008 CERTIFIED COMPANY



The Power of Water Flow

हमारे घर - खेती में
पानी की हर जरूरत को पुरी करे...





440 Volt V6 Submersible Pump Set (H Series)

Pump :
Bowl - S.S. 304 Grade
Impeller - S.S. 410 Grade

Motor :
H.P. - 3.00 to 30.00
Max. Amps. Range - 6 A. to 51 A.
RPM-2880 • Winding Type - Close
Voltage Range : 180 to 415 V.
Rotor - Copper Brazing



440 Volt V6 Submersible Pump Set (Q Series)

Pump :
Bowl - Cast iron
Impeller - S.S. 410 Grade

Motor :
H.P. - 3.00 to 30.00
Max. Amps. Range - 6 A. to 51 A.
RPM-2880 • Winding Type - Close
Voltage Range : 180 to 415 V.
Rotor - Copper Brazing



440 Volt V6 Submersible Pump Set (L Series)

Pump :
Bowl - Cast iron
Impeller - Nylon (With S.S. Neck Ring)

Motor :
H.P. - 3.00 to 30.00
Max. Amps. Range - 6 A. to 51 A.
RPM-2880 • Winding Type - Close
Voltage Range : 180 to 415 V.
Rotor - Copper Brazing



440 V. Janta Model Sub. Pump Set (V67, V68 Series)

Pump :
Bowl - Cast iron
Impeller - S.S. 410 Grade

Motor :
H.P. - 5.00 to 25.00
Max. Amps. Range - 11 A. to 50 A.
RPM-2880 • Winding Type - Close
Voltage Range : 250 to 415 V.
Rotor - Copper Brazing



220 Volt V4 Submersible Pump Set (Z Series)

Pump :
Bowl & Impeller - Noryl : 20 % Glass Filled
Del. Size - 32 mm to 50 mm

Motor :
H.P. - 0.50 to 5.00
Max. Amps. Range - 6 A. to 26 A.
RPM-2880 • Winding Type - Close
Voltage Range : 180 to 220 V.
Rotor - Copper Brazing



220 Volt V4 Submersible Pump Set (L Series)

Pump :
Bowl & Impeller - Noryl : 20 % Glass Filled
Del. Size - 32 mm to 40 mm

Motor :
H.P. - 0.50 to 1.50
Max. Amps. Range - 6 A. to 11.50 A.
RPM-2880 • Winding Type - Close
Voltage Range : 180 to 220 V.
Rotor - Alu.Dia Cast



440 Volt V4 Submersible Pump Set (Z Series)

Pump :
Bowl & Impeller - Noryl : 20 % Glass Filled
Del. Size - 32 mm to 50 mm

Motor :
H.P. - 2.00 to 7.50
Max. Amps. Range - 5.50 A. to 17 A.
RPM-2880 • Winding Type - Close
Voltage Range : 200 to 415 V.
Rotor - Copper Brazing



220 Volt V3 Submersible Pump Set (N Series)

Pump :
Bowl & Impeller - Noryl : 20 % Glass Filled
Del. Size - 32 mm

Motor :
H.P. - 0.50 to 1.50
Max. Amps. Range - 5 A. to 9 A.
RPM-2880, Winding Type - Close
Voltage Range : 180 to 220 V.
Rotor - Copper Brazing



220 Volt Openwell Pump Set

Pump :
Max. Discharge - 54,000 LPH

Motor :
H.P. - 0.50 to 5.00
Max. Amps. Range - 6 A. to 38 A., RPM-2880,
Voltage Range : 180 to 220 V.
Rotor - Copper & Alu.



440 Volt Openwell Pump Set

Pump :
Max. Discharge - 70,000 LPH

Motor :
H.P. - 3.00 to 10.00
Max. Amps. Range - 7 A. to 27 A., RPM-2880,
Voltage Range : 275 to 380 V.
Rotor - Copper & Alu.



440 Volt Openwell Pump Set

Pump :
Max. Discharge - 70,000 LPH

Motor :
H.P. - 1.00 to 10.00
Max. Amps. Range - 7 A. to 27 A., RPM-2880,
Voltage Range : 275 to 380 V.
Rotor - Copper & Alu.

440 Volt Monoblock Pump Set



Max. Dis. - 72,000 LPH
H.P. - 3.00 to 10.00
Motor Seal - Mech. Seal & Glen Rope

Centrifugal Monoblock Pump Set



Max. Dis. - 45,000 LPH
H.P. - 0.50 to 3.00
Phase - Single & Three
Motor Seal - Mech. Seal

Hari Naman Pumps

New Somnath Ind. Area, Surve No. 1, Nr Santkrupa Hotel,
Kothariya, Rajkot-360 022. (Gujarat)
Mo. +91 98982 65399 / +91 70484 08154

Dealer Stamp